

SSR MOTORSPORTS

SSR Motorsports, since 2002 we have been building the products that open up the world of riding.

What sets SSR apart is our focus on bringing cutting edge design, superior engineering, and value for money to the smaller displacement market. We believe that every enthusiast should be able to afford a brand new powersport product from a comprehensive dealer network, with the backing of an expansive distribution center stocked with readily available replacement parts.

Thank you for your interest, whether you are looking for a vehicle for yourself or a vehicle to share the riding experience with your family; whether your interest is ribbons of asphalt or your favorite stretch of dirt road; our knowledgeable and experienced staff is on hand to provide you with the customer service and technical support you need.

OFF-ROAD LINE-UP



SR70C

BASE MODEL DIRT BIKE
72 cc | 4 Stroke
113 lbs. | 57" x 24" x 31"

ENGINE	
Bore And Stroke	47 mm x 41.4 mm
Rated Output	4.69 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm
Ignition	CDI
Starter	Kick
Transmission	Semi-automatic, 4-down

CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.50-10 2.50-10
Frame	Double Bar Steel
Swingarm	Steel, "Straight" Type

DIMENSIONS	
Wheelbase	43 inches
Seat Height	22.5 inches
Ground Clearance	6 inches



SR70AUTO

BASE MODEL DIRT BIKE
72 cc | 4 Stroke
113 lbs. | 53" x 24" x 31"

ENGINE	
Bore And Stroke	47 mm x 41.4 mm
Rated Output	4.69 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm
Ignition	CDI
Starter	Electric
Transmission	Automatic

CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	255 mm Shock
Brake, FR RR	Drum Drum
Tire, FR RR	2.50-10 2.50-10
Frame	Double Bar Steel
Swingarm	Steel, "A" Type

DIMENSIONS	
Wheelbase	39 inches
Seat Height	21.5 inches
Ground Clearance	5 inches



SR110

BASE MODEL DIRT BIKE
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4 mm x 49.5 mm
Rated Output	6.2 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up

CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.75-12 3.00-10
Frame	Steel Backbone
Swingarm	Steel, "Straight" Type

DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	28 inches
Ground Clearance	10 inches



SR110SEM

BASE MODEL DIRT BIKE
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"

ENGINE	
Bore And Stroke	52.4 mm x 49.5 mm
Rated Output	6.2 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm
Ignition	CDI
Starter	Kick
Transmission	Semi-automatic, 4-up

CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.75-12 3.00-10
Frame	Steel Backbone
Swingarm	Steel, "Straight" Type

DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	28 inches
Ground Clearance	10 inches



BUSINESS CARD

All figures based on the latest information at time of publication and subject to change without notice and obligation. Contact your local dealer for specific availability. Obey the law and always wear a dot approved helmet, appropriate eye protection, and proper clothing whenever you ride. Read your owner's manual and inspect your vehicle before riding. Respect the rights of others when you ride, never ride after consuming drugs or alcohol, and never race other vehicles. Vehicle photos and specifications in this brochure reflect models sold in the USA only. Visit www.ssrmotorsports.com for more information. SSR Motorsports, the SSR logo, and SSR model names are trademarks of SSR Motorsports. © 2019 SSR Motorsports. Printed in the USA.



SSR MOTORSPORTS

12825 Alondra Blvd. • Norwalk, CA 90650

Ph: (562) 926-2888 Fx: (562) 926-6999

www.ssrmotorsports.com



OPEN UP YOUR WORLD





SR110DX DELUXE MODEL DIRT BIKE
107 cc | 4 Stroke
122 lbs. | 59" x 29" x 40"



SR125 BASE MODEL DIRT BIKE
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"



SR125SE BASE MODEL DIRT BIKE
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"



SR125AUTO BASE MODEL DIRT BIKE
124 cc | 4 Stroke
129 lbs. | 65" x 29" x 40"



SR110TR TR SERIES DIRT BIKE
107 cc | 4 Stroke
147 lbs. | 63.5" x 27" x 37"



SR125TR TR SERIES DIRT BIKE
124 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"

ENGINE	
Bore And Stroke	52.4 mm x 49.5 mm
Rated Output	6.2 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	265 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.75-12 3.00-10
Frame	Steel Backbone
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	42.5 inches
Seat Height	29 inches
Ground Clearance	10 inches

ENGINE	
Bore And Stroke	54 mm x 54 mm
Rated Output	7.3 hp @ 7,500 rpm
Fuel Supply	Carburetor, 22 mm
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.50-14 3.00-12
Frame	Double Bar Steel
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches

ENGINE	
Bore And Stroke	54 mm x 54 mm
Rated Output	7.3 hp @ 7,500 rpm
Fuel Supply	Carburetor, 22 mm
Ignition	CDI
Starter	Kick
Transmission	Semi-automatic, 4-up
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.50-14 3.00-12
Frame	Double Bar Steel
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches

ENGINE	
Bore And Stroke	54 mm x 54 mm
Rated Output	7.3 hp @ 7,500 rpm
Fuel Supply	Carburetor, 22 mm
Ignition	CDI
Starter	Electric
Transmission	Automatic
CHASSIS	
Front Suspension	Hydraulic, Conventional
Rear Suspension	275 mm Shock
Brake, FR RR	Disc Disc
Tire, FR RR	2.50-14 3.00-12
Frame	Double Bar Steel
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	47 inches
Seat Height	30 inches
Ground Clearance	10.5 inches

ENGINE	
Bore And Stroke	52.4 mm x 49.5 mm
Rated Output	7.0 hp @ 7,500 rpm
Fuel Supply	Carburetor, 16 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Semi-automatic, 4-up
CHASSIS	
Front Suspension	Rebound Adjustable Forks, Inverted
Rear Suspension	280 mm Shock, 850 pounds/inch
Brake, FR RR	Disc Disc
Tire, FR RR	60/100-14 80/100-12
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	44.5 inches
Seat Height	28.4 inches
Ground Clearance	10 inches

ENGINE	
Bore And Stroke	54 mm x 54 mm
Rated Output	8.5 hp @ 7,500 rpm
Fuel Supply	Carburetor, 22 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	Hydraulic, Inverted
Rear Suspension	290 mm Shock, 850 pounds/inch
Brake, FR RR	Disc Disc
Tire, FR RR	60/100-14 80/100-12
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches



SR125TR-BW TR SERIES DIRT BIKE
124 cc | 4 Stroke
159 lbs. | 70" x 29.5" x 44"



SR140TR TR SERIES DIRT BIKE
140 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"



SR140TR-BW TR SERIES DIRT BIKE
140 cc | 4 Stroke
159 lbs. | 70" x 29.5" x 44"



SR170TR TR SERIES DIRT BIKE
169 cc | 4 Stroke
157 lbs. | 66" x 29.5" x 43"



SR170TX TX SERIES DIRT BIKE
169 cc | 4 Stroke
149 lbs. | 68" x 29.5" x 42"



SR150 MID-SIZE COMPETITION BIKE
150 cc | 4 Stroke
227 lbs. | 73.2" x 31" x 44"

ENGINE	
Bore And Stroke	54 mm x 54 mm
Rated Output	8.5 hp @ 7,500 rpm
Fuel Supply	Carburetor, 22 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	Hydraulic, Inverted
Rear Suspension	290 mm Shock, 850 pounds/inch
Brake, FR RR	Disc Disc
Tire, FR RR	70/100-17 90/100-14
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	49 inches
Seat Height	33 inches
Ground Clearance	13 inches

ENGINE	
Bore And Stroke	55 mm x 59 mm
Rated Output	12.0 hp @ 8,500 rpm
Fuel Supply	Carburetor, 26 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	Disc Disc
Tire, FR RR	60/100-14 80/100-12
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	10.2 inches

ENGINE	
Bore And Stroke	55 mm x 59 mm
Rated Output	12.0 hp @ 8,500 rpm
Fuel Supply	Carburetor, 26 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	Disc Disc
Tire, FR RR	70/100-17 90/100-14
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	49 inches
Seat Height	33 inches
Ground Clearance	13 inches

ENGINE	
Bore And Stroke	62 mm x 56 mm
Rated Output	15.8 hp @ 9,000 rpm
Fuel Supply	Carburetor, 26 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted
Rear Suspension	290 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	Disc Disc
Tire, FR RR	60/100-14 80/100-12
Frame	Double Bar Steel w/ Sub-frame
Swingarm	Steel, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	32 inches
Ground Clearance	12 inches

ENGINE	
Bore And Stroke	62 mm x 56 mm
Rated Output	15.8 hp @ 9,000 rpm
Fuel Supply	Carburetor, 26 mm Mikuni
Ignition	CDI
Starter	Kick
Transmission	Manual, 4-up
CHASSIS	
Front Suspension	R/C Adjustable Forks, Inverted, 8" Trvl.
Rear Suspension	275 mm DNM R/C Adjustable Shock
Brake, FR RR	Disc Disc
Tire, FR RR	60/100-14 80/100-12
Frame	Chromoly Steel w/ Sub-frame
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	48 inches
Seat Height	30.5 inches
Ground Clearance	10.5 inches

ENGINE	
Bore And Stroke	62 mm x 49.6 mm
Rated Output	13.4 hp @ 9,000 rpm
Fuel Supply	Carburetor, 28 mm
Ignition	CDI
Starter	Electric / Kick
Transmission	5-speed Manual, 1-down, 4-up
CHASSIS	
Front Suspension	Hydraulic, Inverted, 230 mm Trvl.
Rear Suspension	450 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	220 mm Disc 190 mm Disc
Tire, FR RR	70/100-17 90/100-14
Frame	Cast Steel w/ Formed Steel Tube
Swingarm	Steel - Box Section
DIMENSIONS	
Wheelbase	51.5 inches
Seat Height	33.5 inches
Ground Clearance	11 inches



SR189 MID-SIZE COMPETITION BIKE
189 cc | 4 Stroke
236 lbs. | 74.4" x 31" x 45.7"



SR250S FULL-SIZE COMPETITION BIKE
249.6 cc | 4 Stroke
260 lbs. | 91" x 32.5" x 51"



SR300S FULL-SIZE COMPETITION BIKE
300 cc | 4 Stroke
256 lbs. | 85.4" x 32.3" x 50"



SR450S FULL-SIZE COMPETITION BIKE
449 cc | 4 Stroke
265 lbs. | 91" x 32.5" x 51"



XF250 DUAL SPORT MOTORCYCLE
249 cc | 4 Stroke
328 lbs. | 81" x 30.5" x 44"



SRUT70RS YOUTH ATV
168.9 cc | 1-cyl., Horizontal Type
540 lbs. | 98" x 48" x 60"

ENGINE	
Bore And Stroke	65.5 mm x 56.2 mm
Rated Output	15.4 hp @ 8,500 rpm
Fuel Supply	Carburetor, 30 mm
Ignition	CDI
Starter	Electric / Kick
Transmission	5-speed Manual, 1-down, 4-up
CHASSIS	
Front Suspension	R/C Adj. Forks, Inverted, 255 mm Trvl.
Rear Suspension	450 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	240 mm Disc 240 mm Disc
Tire, FR RR	70/100-19 90/100-16
Frame	Cast Steel w/ Formed Steel Tube
Swingarm	Steel - Box Section
DIMENSIONS	
Wheelbase	52 inches
Seat Height	35 inches
Ground Clearance	12.4 inches

ENGINE	
Bore And Stroke	77 mm x 53.6 mm
Rated Output	25.8 hp @ 9,000 rpm
Fuel Supply	Carburetor, 34 mm
Ignition	CDI
Starter	Electric / Kick
Transmission	5-speed Manual, 1-down, 4-up
CHASSIS	
Front Suspension	R/C Adj. Forks, Inverted, 315 mm Trvl.
Rear Suspension	Spring Preload & Reb. Adjustable Shock
Brake, FR RR	240 mm Disc 240 mm Disc
Tire, FR RR	80/100-21 100/90-18
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	59 inches
Seat Height	37.8 inches
Ground Clearance	12.2 inches

ENGINE	
Bore And Stroke	82 mm x 53.6 mm
Rated Output	30.8 hp @ 9,500 rpm
Fuel Supply	Carburetor, 35 mm
Ignition	CDI
Starter	Electric / Kick
Transmission	6-speed Manual, 1-down, 5-up
CHASSIS	
Front Suspension	R/C Adj. Forks, Inverted, 250 mm Trvl.
Rear Suspension	480 mm Spring Preload & Reb. Adj. Shock
Brake, FR RR	240 mm Disc 240 mm Disc
Tire, FR RR	80/100-21 100/90-19
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	57 inches
Seat Height	37.4 inches
Ground Clearance	11.4 inches

ENGINE	
Bore And Stroke	96 mm x 62.1 mm
Rated Output	43.5 hp @ 7,500 rpm
Fuel Supply	Carburetor, 36 mm
Ignition	CDI
Starter	Electric / Kick
Transmission	5-speed Manual, 1-down, 4-up
CHASSIS	
Front Suspension	R/C Adj. Forks, Inverted, 315 mm Trvl.
Rear Suspension	Spring Preload & Reb. Adjustable Shock
Brake, FR RR	240 mm Disc 240 mm Disc
Tire, FR RR	80/100-21 110/100-18
Frame	Aluminum Alloy
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	59 inches
Seat Height	37.8 inches
Ground Clearance	12.2 inches

ENGINE	
Bore And Stroke	72 mm x 61.2 mm
Rated Output	18.1 hp @ 7,000 rpm
Fuel Supply	Carburetor, 26 mm
Ignition	CDI
Starter	Electric
Transmission	5-speed Manual, 1-down, 4-up
CHASSIS	
Front Suspension	Compression Adjustable Forks, Inverted
Rear Suspension	Standard Coil Spring Shock
Brake, FR RR	250 mm Disc 240 mm Disc
Tire, FR RR	4.60-18 5.10-17
Frame	Steel
Swingarm	Aluminum Alloy, "Straight" Type
DIMENSIONS	
Wheelbase	57 inches
Seat Height	35 inches
Ground Clearance	8 inches

ENGINE	
Bore And Stroke	61 mm x 57.8 mm
Rated Output	11.1 hp @ 8,000 rpm
Rated Torque	8.1 ft lb @ 6,000 rpm
Fuel Supply	Carburetor, 30 mm
Drive System	RWD; Chain
Transmission	Belt + Chain Drive w/ CVT (F-N-R)
CHASSIS	
Front Suspension	Double A-arm
Rear Suspension	Swingarm
Brake, FR RR	Disc Disc
Tire, FR RR	21x7-10 22x10-10
DIMENSIONS	
Wheelbase	72 inches
Ground Clearance	7 inches
Fuel Tank	29.0 gallons
Weight Capacity	330 pounds
Cargo Bed	33 x 16 x 6 inches